




BERA GRAVEL EDGE 'L'

Gravel Edging & Borders



BERA[®]



BERA® Gravel Edge 'L'

Gravel path and driveways using BERA® Gravel Fix stabilisation require edging to prevent the sheets from shifting. With Gravel Edge 'L' it is easy and fast to arrange either straight or curvy paths or light traffic driveways. Accessories like connectors and pins are available. BERA® Gravel Edge 'L' is light in weight, easy to cut with scissors to create your own design without virtually any limit.

BERA® Gravel Edge 'L' is made of polypropylene and is fully recyclable. Using green power and employing disable staff supports our strive to care about people and environment.

TECHNICAL SPECIFICATIONS

Product	: BERA® Gravel Edge 'L'
Colour	: Black or white
Material	: Polypropylene
Weight	: 0.22/m
Dimension	: 4.5 x 4.5 cm
Available length	: 6.0, 2.4, 1.2 m
Product Safety	: REACH
Product Standard	: ISO9001
UV and frost	: Protected
Packing	: Bundles



Connector Kits



Installation Instructions



Cut the triangle strip to enable the edging to be used in curvy designs or creating bends. Extend each piece of BERA® Gravel Edge 'L' with the optional connector kit. Put the connector at the back of two pieces of edging, so the connector will be invisible. Connect them by drilling holes and fasten them by the screws.



After final positioning of the edges, fix them to the soil using the optional pins. For soft soil use longer or other fixation methods. Instructions of installation are guidance only and subject to local rules and regulations.

Contact:

BERA B.V. (The Netherlands)
BERA B.V. (Germany)
BERA Sarl (France)
BERA B.V. (Africa)

T: +31 (0) 33 257 0302
T: +49 (0) 30 78 71 68 85
T: +33 (0) 9 81 12 76 58
T: +27 83 449 3954

E: info@bera-bv.com
E: kontakt@bera-bv.com
E: info@bera-sarl.fr
E: franko@bera-bv.com



www.bera-bv.com